

MS390 Datasheet

Overview

The Meraki MS390 addresses the most demanding enterprise applications by combining the simplicity of the Meraki dashboard with powerful switching hardware. To satisfy high-bandwidth applications and the deployment of high-speed 802.11ax/wifi-6 access points, the MS390 provides multigigabit ports, 480G stacking, and modular 10/40G uplinks. The MS390 delivers resiliency with fast stack convergence and StackPower. The MS390 provides Adaptive Policy using an over-the-wire tag which segments traffic into security groups to deliver scalable security. The MS390 is integrated under the Meraki dashboard to provide a simply powerful solution to the most demanding wired access applications.

Adaptive Policy provides simple & scalable security policies to segment traffic using Security Groups. Security Groups are created in the dashboard using natural language such as "IOT device" & "Guest." The security policy intent (e.g., Permit or Deny) is then simply provisioned between Security Groups which results in the segmentation of each group's traffic. By making security policy management intuitive and scalable relative to legacy IP-address based Access Control Lists, Adaptive Policy empowers operators to confidently secure their network traffic independent of future network changes.

By pooling & distributing power across MS390s using a series of StackPower cables, StackPower provides simple and resilient power distribution across the stack.



Models

Number of Ports	Model	Description
	MS390-24-HW	24-port Gbe switch
	MS390-24P-HW	24-port Gbe PoE+ switch

24 Ports	MS390-24U-HW	24-port Gbe UPoE switch
	MS390-24UX-HW	24-port mGbe UPoE switch
48 Ports	MS390-48-HW	48-port Gbe switch
	MS390-48P-HW	48-port Gbe PoE+ switch
	MS390-48U-HW	48-port Gbe UPoE switch
	MS390-48UX-HW	36-port 2.5Gbe + 12-port mGbe UPoE switch
	MS390-48UX2-HW	48-port 5Gbe UPOE switch

Features

Category	Features
Highlights	<ul style="list-style-type: none"> • Layer-3 • 40G or 10G modular uplink options on all models • mGig support • Dual Dedicated 120G Hardware Stacking Ports • PoE+ and UPoE Support • StackPower
Management	<ul style="list-style-type: none"> • Managed via Cisco Meraki Dashboard • Zero-touch remote provisioning (no staging needed) • Basic configuration capability via local management page • Detailed historical per-port and per-client usage statistics • Operating System, device, and hostname fingerprinting • Automatic firmware upgrades with scheduling control • SNMP and SYSLOG support for integration with other network management solutions*
Remote Diagnostics	<ul style="list-style-type: none"> • Email, SMS and Mobile push notification alerts¹ • Ping, traceroute, cable testing, and link failure detection with alerting • Remote packet capture • Dynamic and interactive network discovery and topology • Combined event and configuration change logs with instant search
Stacking	<ul style="list-style-type: none"> • Physically stack up to 8 switches with 480 Gbps of stacking bandwidth on all models • Virtual stacking supports thousands of switch ports in a single logical stack for unified management, monitoring, and configuration • Faster convergence

	<ul style="list-style-type: none"> StackPower
Ethernet Switching Capabilities	<ul style="list-style-type: none"> 802.1p Quality of Service, 8 queues (w/ 6 configurable for DSCP-to-CoS mapping) 802.1Q VLAN and trunking support for up to 4,094 VLANs (1000 active VLANs with STP enabled) Single Instance of 802.1s Multiple Spanning Tree Protocol (interoperable with RSTP, STP, PVST, RPVST) STP Enhancements: BPDU guard, Root guard, Loop guard, UDLD Broadcast storm control 802.1ab Link Layer Discovery Protocol (LLDP) and Cisco Discovery Protocol (CDP) 802.3ad Link aggregation with up to 8 ports per aggregate, Multichassis aggregates supported on stacked switches Port mirroring IGMP snooping for multicast filtering MAC Forwarding Entries: 32K
Layer 3	<ul style="list-style-type: none"> Static routing, OSPFv2 Multicast routing (PIM-ASM) Warm Spare (VRRP) DHCP Server, DHCP Relay
Security	<ul style="list-style-type: none"> Integrated multi-factor authentication for Dashboard management Role-based access control (RBAC) with granular device and configuration control Corporate wide password policy enforcement IEEE 802.1X RADIUS and MAB, hybrid authentication and RADIUS server testing Single-Host/Multi-Domain/Multi-Host/Multi Authentication Port security: Sticky MAC, MAC whitelisting DHCP snooping, detection and blocking, Dynamic ARP Inspection IPv4 and IPv6 ACLs Secure Connect * Adaptive Policy *

 * Available in a future software release

MS390 Licensing

MS390 license structure includes two feature tiers: Enterprise and Advanced. The MS390 also introduces a new and simpler license to hardware mapping, specifically 24-port or 48-port licenses. As with all MS, every MS390 license is available in 1, 3, 5, 7, and 10 year terms.

MS390 License Structure	24-Port Model	48-port Model
Advanced Features	LIC-MS390-24A	LIC-MS390-48A

Enterprise Features

LIC-MS390-24E

LIC-MS390-48E

The features available with advanced licensing are:

- Adaptive policy *
- Greater than 1,000 routes for OSPF



* Available in a future software release

Context and Comparisons

Description	24 Port Models			48 Port Models		
	MS350-24X	MS355-24X2	MS390-24UX	MS350-48FP	MS355-48X2	MS390-48UX2
1GbE RJ45	16	-	-	48	24	-
mGbE RJ45	8	24	24	-	24	48
10GbE SFP+	4	4	Modular	4	4	Modular
40GbE QSFP+	n/a	2	Modular	-	2	Modular
Hardware Stack Port	2x 40G	2x 100G	2x 120G	2x 40G	2x 100G	2x 120G
Management Interface	1	1	1	1	1	1
Hot Swap PS	Yes, Dual	Yes, Dual	Yes, Dual	Yes, Dual	Yes, Dual	Yes, Dual
Hot Swap Fans	Yes, 2x	Yes, 3x	Yes, 3x	Yes, 2x	Yes, 3x	Yes, 3x
Layer 3 Routing	Yes	Yes	Yes	Yes	Yes	Yes
UPoE Capable	Yes, 740W	Yes, 740W	Yes, 560W	Yes, 740W	Yes, 740W	Yes, 645W
Max Switching Capacity	176 Gbps	640 Gbps	640 Gbps	176 Gbps	688 Gbps	640 Gbps
Max Stacking Bandwidth	160 Gbps	400 Gbps	480 Gbps	160 Gbps	400 Gbps	480 Gbps

Technical Breakdown

Interfaces Specifications

Model	Interfaces	Uplink 10/40GbE (SFP+, QSFP+)	120G Hardware Stack Port	Dedicated Management Interface	PoE/ UPoE Capabilities
MS390-24-HW	24 x 1GbE RJ45	Modular	2	1	n/a
MS390-24P-HW	24 x 1GbE RJ45	Modular	2	1	PoE
MS390-24U-HW	24 x 1GbE RJ45	Modular	2	1	UPoE
MS390-24UX-HW	24 x mGbE RJ45	Modular	2	1	UPoE
MS390-48-HW	48 x 1GbE RJ45	Modular	2	1	n/a
MS390-48P-HW	48 x 1GbE RJ45	Modular	2	1	PoE
MS390-48U-HW	48 x 1GbE RJ45	Modular	2	1	UPoE
MS390-48UX-HW	36 x 100M/1G/2.5G + 12 x 100M/1G/2.5G/5G/10G	Modular	2	1	UPoE
MS390-48UX2-HW	48 x 100M/1G/2.5G/5G	Modular	2	1	UPoE



All models are available with modular uplinks that have been listed under the [Accessories](#) list. For supported SFP modules please refer the [SFP Datasheet](#).

Physical Specifications

Model	Dimensions (h x w x d) W/ Default Power Supply	Weight	Mount Type	Hot Swap Fans	Operating Temperature	Humidity
MS390-24-HW	1.73" x 17.5" x 17.7" (4.4 x 44.5 x 44.9cm)	16.03 lb (7.27 kg)	1U Rack Mount	Yes, 3x	-5°C to 45°C	5 to 90%
MS390-24P-HW	1.73" x 17.5" x 17.7" (4.4 x 44.5 x 44.9cm)	16.33 lb (7.4 kg)	1U Rack Mount	Yes, 3x	-5°C to 45°C	5 to 90%

MS390-24U-HW	1.73" x 17.5" x 19.2" (4.4 x 44.5 x 44.8cm)	16.63 lb (7.54 kg)	1U Rack Mount	Yes, 3x	-5°C to 45°C	5 to 90%
MS390-24UX-HW	1.73" x 17.5" x 20.2" (4.4 x 44.5 x 51.3cm)	18.18 lb (8.25 kg)	1U Rack Mount	Yes, 3x	-5°C to 45°C	5 to 90%
MS390-48-HW	1.73" x 17.5" x 17.7" (4.4 x 44.5 x 44.9cm)	16.43 lb (7.45 kg)	1U Rack Mount	Yes, 3x	-5°C to 45°C	5 to 90%
MS390-48P-HW	1.73" x 17.5" x 17.7" (4.4 x 44.5 x 44.9cm)	16.73 lb (7.59 kg)	1U Rack Mount	Yes, 3x	-5°C to 45°C	5 to 90%
MS390-48U-HW	1.73" x 17.5" x 19.2" (4.4 x 44.5 x 48.8cm)	17.03 lb (7.72 kg)	1U Rack Mount	Yes, 3x	-5°C to 45°C	5 to 90%
MS390-48UX-HW	1.73" x 17.5" x 22.2" (4.4 x 44.5 x 56.4cm)	20.50 lb (9.34 kg)	1U Rack Mount	Yes, 3x	-5°C to 45°C	5 to 90%
MS390-48UX2-HW	1.73" x 17.5" x 22.2" (4.4 x 44.5 x 56.4cm)	20.05 lb (9.09 kg)	1U Rack Mount	Yes, 3x	-5°C to 45°C	5 to 90%

Performance

Model	Switching Capacity	Stacking Bandwidth	Forwarding rate
MS390-24-HW	208 Gbps	480 Gbps	154.76 Mpps
MS390-24P-HW	208 Gbps	480 Gbps	154.76 Mpps
MS390-24U-HW	208 Gbps	480 Gbps	154.76 Mpps
MS390-24UX-HW	640 Gbps	480 Gbps	476.19 Mpps
MS390-48-HW	256 Gbps	480 Gbps	190.48 Mpps
MS390-48P-HW	256 Gbps	480 Gbps	190.48 Mpps
MS390-48U-HW	256 Gbps	480 Gbps	190.48 Mpps
MS390-48UX-HW	580 Gbps	480 Gbps	431.54 Mpps

MS390-48UX2-HW

640 Gbps

480 Gbps

476.19 Mpps

Power Options and Specifications

Model	Default Power Supply	Hot Swap Power Supply	Available PoE W/ Primary PS	Available PoE W/ Secondary PS***	Power Load (idle/max)
MS390-24-HW	MA-PWR-350WAC**	Yes, Dual	n/a	n/a	79.2 / 99 W
MS390-24P-HW	MA-PWR-715WAC**	Yes, Dual	445W	720W	84.1 / 554.4 W
MS390-24U-HW	MA-PWR-1100WAC	Yes, Dual	830W	1440W	85.4 / 990.3 W
MS390-24UX-HW	MA-PWR-1100WAC	Yes, Dual	560W	1440W	162.7 / 809.9 W
MS390-48-HW	MA-PWR-350WAC**	Yes, Dual	n/a	n/a	83.9 / 109.9 W
MS390-48P-HW	MA-PWR-715WAC**	Yes, Dual	437W	1152W	92.6 / 555 W
MS390-48U-HW	MA-PWR-1100WAC	Yes, Dual	822W	1800W	145 / 844.9 W
MS390-48UX-HW	MA-PWR-1100WAC	Yes, Dual	490W	1590W	218.5 / 785.5 W
MS390-48UX2-HW	MA-PWR-1100WAC	Yes, Dual	645W	1745W	157.9 / 843.8 W



** Upgrade options to 715W and 1100W PSU are available.

*** The PoE values are provided considering the secondary PS to be the default power supply of the respective model.

What's included

Model	Package Contents
MS390-24-HW	1 x Power Supply (MA-PWR-350WAC), Rack mount brackets and screw kit, 3 x Pre-Installed Fans, Cable guide
MS390-24P-HW	1 x Power Supply (MA-PWR-715WAC), Rack mount brackets and screw kit, 3 x Pre-Installed Fans, Cable guide

MS390-24U-HW	1 x Power Supply (MA-PWR-1100WAC), Rack mount brackets and screw kit, 3 x Pre-Installed Fans, Cable guide
MS390-24UX-HW	1 x Power Supply (MA-PWR-1100WAC), Rack mount brackets and screw kit, 3 x Pre-Installed Fans, Cable guide
MS390-48-HW	1 x Power Supply (MA-PWR-350WAC), Rack mount brackets and screw kit, 3 x Pre-Installed Fans, Cable guide
MS390-48P-HW	1 x Power Supply (MA-PWR-715WAC), Rack mount brackets and screw kit, 3 x Pre-Installed Fans, Cable guide
MS390-48U-HW	1 x Power Supply (MA-PWR-1100WAC), Rack mount brackets and screw kit, 3 x Pre-Installed Fans, Cable guide
MS390-48UX-HW	1 x Power Supply (MA-PWR-1100WAC), Rack mount brackets and screw kit, 3 x Pre-Installed Fans, Cable guide
MS390-48UX2-HW	1 x Power Supply (MA-PWR-1100WAC), Rack mount brackets and screw kit, 3 x Pre-Installed Fans, Cable guide

Optional Accessories

Accessory	Description	Supported Models
MA-PWR-350WAC	350W AC Power Supply	MS390-24-HW, MS390-48-HW
MA-PWR-715WAC	715W AC Power Supply	All Models
MA-PWR-1100WAC	1100W AC Power Supply	All Models
MA-MOD-2X40G	2 x 40G Uplink Module	All Models
MA-MOD-4X10G	4 x 10G Uplink Module	All Models
MA-MOD-8X10G	8 x 10G Uplink Module	All Models
MA-CBL-120G-50CM	Meraki 120G Stacking Cable, 0.5 Meter	All Models
MA-CBL-120G-1M	Meraki 120G Stacking Cable, 1 Meter	All Models
MA-CBL-120G-3M	Meraki 120G Stacking Cable, 3 Meter	All Models
MA-CBL-SPWR-30CM	Meraki MS390 30CM Power-Stack Cable	All Models
MA-CBL-SPWR-150CM	Meraki MS390 150CM Power-Stack Cable	All Models
MA-FAN-16K2	System Fan	All Models
MA-RCKMNT	Meraki MS390 Rack Mount Kit	All Models

Regulations and Compliance

Electromagnetic	FCC Part 15 (CFR 47) Class A, ICES-003 Class A, CISPR22 Class A, CNS13438, EN 300 386 V1.6.1, EN 55022 Class A, EN
------------------------	--

Compatibility	61000-3-2, EN61000-3-3, KN 32, TCVN 7189 Class A, EN 55032 , CISPR 32 Class A, V-2/2015.04, V-3/2015.04, VCCI-CISPR 32
Certifications	Class A, CISPR24, EN 300 386 V1.6.1, EN 55024, KN35, TCVN 7317
Safety	CAN/CSA-C22.2 No. 60950-1, UL 60950-1, EN 60950-1, IEC 60950-1, AS/NZS 60950.1
Environmental	Reduction of Hazardous Substances (RoHS)
Warranty	Full lifetime hardware warranty with next-day advanced replacement included

MTBF Rating

Model	MTBF at 25°C
MS390-24-HW	314,790
MS390-24P-HW	299,000
MS390-24U-HW	238,410
MS390-24UX-HW	214,760
MS390-48-HW	305,870
MS390-48P-HW	277,770
MS390-48U-HW	227,410
MS390-48UX-HW	202,160
MS390-48UX2-HW	198,647

Installation Guide

For instructions on how to install and configure the MS390 series switch please refer the [MS390 Series Installation Guide](#)