

H2S IP Phone

The new Fanvil H2S IP Phone is a Hotel phone with succinct design and high cost performance greatly improve production efficiency.

Highlights

- ✓ Concise and fashionable product appearance
- ✓ Economical and Environmental friendly product concepts
- ✓ Easy installation and configuration
- ✓ Support for fast ethernet - adaptive 10/100mbps network port, support PoE power supply.
- ✓ High Interoperability - Compatible with major platforms: 3CX, Broadsoft, Elastix, Asterisk, Xorcom, etc.



| Model | Screen | Network | PoE | Supply Power |
|-------|--------|------------|-----|--------------|
| H2S | N/A | 10/100Mbps | ✓ | ✓ |

Generic

- 1 SIP Line
- POE Enable or Optional External Power Supply
- Handset(HS)
- Wall installation
- Economical and Environmental friendly package
- Industrial Standard Certifications: CE/FCC

Call Features

- Call out / answer
- Call Hold / Resume
- Call Transfer(Attended/Unattended)
- Redial
- Hot Line

Phone Features

- Call logs with missed calls/ incoming calls/ outgoing calls. Max support 600 records(web)
- Dial without registration
- Action URL / Active URI
- Web dial

Audio

- Narrowband CODEC: G.711a/u, G.723.1, G.726-32K, G.729AB
- Acoustic echo cancellation (AEC) – Hands-free Mode, 96ms tail-length
- Dynamic Adaptive Jitter Buffer up to 300ms
- DTMF: In-band, Out-of-Band – DTMF (RFC2833) / SIP INFO

Networking

- 10/100Mbps Ethernet
- IP Configuration: Static / DHCP / PPPoE
- Network Access Control: 802.1x
- VPN: L2TP / OpenVPN
- VLAN
- QoS

Protocols

- SIP2.0 over UDP/TCP/TLS
- RTP/RTCP/SRTP
- STUN
- DHCP
- PPPoE
- 802.1x
- L2TP
- OpenVPN
- SNTP
- FTP/TFTP
- HTTP/HTTPS
- TR069

Deployment & Maintenance

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR069
- Web Management Portal
- Web-based Packet-dump
- Configuration Export / Import
- Firmware Upgrade
- syslog

Physical Specifications

- Keypad: 17 keys, including
 - 12 Standard Phone Digits keys
 - 4 Function keys (Hold, Release, Transfer, Redial)
 - 1 DSS key
- HD Handset (RJ9) x1
- Standard RJ9 Handset Wire x1
- RJ9 Phone Jacket x1: Handset x1
- RJ45 Ethernet Port x1: Network x1 (802.3AF POE Class 1 Enabled),
 - DC Power Input: 12V / 0.5A
 - Power Consumption: Idle – 1.6~2.3W, Peak – 2.6~3.3W
 - Working Temperature: 0~40°C
 - Working Humidity: 10~65%
 - Color: Black
 - Device Dimensions: 221.5x96x59mm
 - Gift Box Dimensions: 302x105x67mm
 - Outer CTN Dimensions: 445x355x325mm (20 PCS)

Company Profile:

Fanvil Technology Co., Ltd. is a professional developer and manufacturer of VoIP products. Fanvil provides VoIP communication devices solutions for small and medium sized businesses, as well as large mission-critical enterprise environments

Compatibility List:

