

Hotel Phone H5



Company Profile: Fanvil Technology Co., Ltd. is a professional developer and manufacturer of VoIP products. Fanvil provides VoIP communication devices solutions for small and medium sized businesses, as well as large mission-critical enterprise environments.

Phone Features

- vxworks OS
- Support SIP2.0 (RFC3261) and correlative RFCs
- SIP support 1 SIP servers, and backup SIP proxy servers
- Supports SIP UDP / TCP/ TLS
- SIP support SIP domain, SIP authentication (none, basic, MD5) , DNS name of server, Peer to Peer / IP Call

Key Features

- 6 Soft keys programmable
- Multi languages displayed(web)

Audio

- HD voice: HD handset
- Codec: G.711A/U, G.723.1 high/low, G.729AB, G.722, G.726-32
- DTMF: in-band, RFC2833 and SIP INFO
- Full-duplex Acoustic Echo Canceller (AEC) – Hands-free Mode, 96ms tail-length
- Voice Activity Detection (VAD) / Comfort Noise Generation (CNG) / Background Noise Estimation (BNE) / Noise Reduction (NR)
- Packet Loss Concealment (PLC)
- Dynamic Adaptive Jitter Buffer up to 300ms
- DTMF: In-band, Out-of-Band – DTMF-Relay(RFC2833) / SIP INFO

Advanced Features

- Call transfer (unattended/ attended/ semi-attended)
- Call holding
- Call waiting
- Redial
- Call completion
- Predial
- MWI
- Flexible dial plan
- Barring function for outgoing calls
- Do not disturb
- Auto answer
- CLIR(rejects anonymous calls)
- CLIP(to make an anonymous call)
- Dial without registration
- Call logs with missed calls/ incoming calls/ outgoing calls. Each support 300 records(Web)
- Speed Dial
- Hotline/Warm-line
- Password dial

- DTMF hidden
- Action URL/ active URI
- Multicast
- Web dial
- Emergency call

Network/ Security Features

- WAN / LAN: 10/100M Ethernet ports (Bridge mode)
- IP Configuration: Static / DHCP / PPPoE
- Network Access Control: 802.1x
- VPN: L2TP (Basic Unencrypted) / OpenVPN
- VLAN
- QoS

Deployment & Maintenance

- Auto-Provisioning via FTP/TFTP/HTTP/HTTPS/DHCP OPT66/SIP PNP/TR069
- Web Management Portal
- Web-based Packet Dump
- Configuration Export / Import
- Firmware Upgrade
- Syslog

Physical Specifications

- LCD: 3.5inch (480x320) color screen
- Adapter Input: AC100-240V
- Adapter Output: DC 5V/1A
- WAN Port -10/100 BASE-T RJ-45 for LAN
- LAN Port-10/100 BASE-T RJ-45 for PC
- Handset: RJ9
- Power consumption: IDLE: 2.5W Active: 2.8W
- Operation Temperature: 0~40 °C
- Relative Humidity: 10~65%
- Main Chipset: Broadcom
- SDRAM: 16MB
- FLASH: 8MB
- Dimension: 213x170x130 mm

Certification

